

ROTAMAT® Wash Drum RoSF 9 / RoFAS



Efficient and reliable coarse material separation:

- Grit from WWTPs and sewer systems
- Road refuse and oil grit
- Septic sludge
- Industrial applications



Design and function

RoSF 9 – the ROTAMAT® Wash Drum for separation of grit from WWTPs and sewer systems, road refuse and oil grit:

While wash water is added to pre-wash and homogenise the raw material within the ROTAMAT® Wash Drum, the perforated plate of the Wash Drum retains all particles > 10 mm, which are dewatered and then discharged into a skip. Since only coarse material > 10 mm is separated, the volume of the resultant residues is vastly reduced with virtually the complete mineral material being further treated in the down-stream COANDA Grit Washer. The resultant coarse material can then be further separated into a mineral and organic fraction by means of a coarse material washer.

RoFAS – the ROTAMAT® Wash Drum as a sludge acceptance plant

Rotating high-performance screening drum for extreme applications. Reliable, clog-free solids transport through forced guided material transport within the drum. Solids washing and dewatering by means of a subsequent HUBER WAP Screenings Wash press.

Benefits

- ➤ High solids throughput even with problematic material (tresses, grease, stones)
- ➤ High hydraulic capacity even with high solids contents
- ➤ Defined separation size due to two-dimensional screening
- ➤ Feeding from a conveyor, through a launder channel or pressure line
- ➤ Completely encased unit
- ➤ Insensitive to coarse material
- > 3 to 100 mm separation size
- > Screened wastewater can be used as wash water
- > Short tanker vehicle emtpying times
- ➤ Optional simultaneous emptying of several vehicles
- ➤ Minimum wear, reduced maintenance
- Compact, space-saving design
- > Low energy demand
- ➤ Manufactured entirely of stainless steel for maximum corrosion resistance

>>> Installation examples



ROTAMAT® Wash Drum for washout and separation of all coarse material > 10 mm



50 I screenings removed per rotation

HUBER SE

Industriepark Erasbach A1 \cdot D-92334 Berching Phone: $+49-8462-201-0\cdot$ Fax: +49-8462-201-810

info@huber.de · Internet: www.huber.de

Subject to technical modification 1,0 / 2 – 8.2008 – 7.2008

ROTAMAT® Wash Drum RoSF 9 / RoFAS